



MASTER CHEMICALS TECHNOLOGY

MC- ALKI PAINT -AL

Aluminum alkyd paint

Description:

MC - Alki Paint - AL is modified alkyd out door and in door coating for steel .

Uses:

MC – Alki Paint – AL is used as protective coating for steel surface.

Advantages:

- ◆ High weathering
- ◆ High abrasion resistance.
- ◆ Anticorrosive.
- ◆ Fast dry.
- ◆ Directly used on the metal surface (No need for a primer coat).
- ◆ High heat reflection and reduces heat absorption.

Technical Data:

Drying time	: 1 -1.5 hr at 25 C°
Solids by volume	: 50 %
Density	: 0.95 ± 0.02 gm / cm ³ at 25 C°
Theoretical consumption rate	: 6.6 m ² /L (75 μ)
Shelf life	: 12 months
Package	: 5, 20 kg pails

Method statement:

Surface preparation:

The surface must be clean and free from oil and grease.

Method of application:

MC – Alki Paint – AL is applied by brush, roller and spray. In case of applying two coats first coat should be dry before applying the second one.

Cleaning:

For cleaning tools and equipments use a suitable thinner

Safety precautions:

The following notes should be considered when using **MC – Alki Paint - AL**:

- ◆ Take precautions to prevent material entering the eyes
- ◆ Take precautions to avoid skin contact
- ◆ Provide adequate ventilation
- ◆ Keep away from sparks and flames.

*For more details contact **Master Chemicals Technology** technical department*

Or visit our website www.mc.com.eg

Master Chemicals Technology

11 Ahmed Kamal str, - Heliopolis

Tel / Fax : 26244491 / 26244492

Mob : 01001615868